3M[™] Volition[™] Cat.6 UTP ID Patchcord



Part of 3M Network Solutions, ICategory 6 ID patch cords are compliant with TIA 568-C.2 Category 6 hardware performance.

The patch cords are supplied in lengths of 1, 2, 3, 5 metres in a number of different colours. The patch cords are available in PVC or LSOH.

Features

- Category 6 TIA 568-C.2 Hardware Performance
- Built in tracing LED
- Protected Latch

Benefits

- Optimized for use with 3M RJ45 UTP Jacks and Category 6 cables
- Easy patchcord management
- Protects latch from damage snag proof



Specification

Features

Categirt 6 performance passes TIA/EIA/568C.2 UL94V-2 fire retardant plastic plug

Technical characteristics

Cable diameter : 6.0± 0.2mm

Copper Diameter: wire gauge AWG 24
Minimum bend radius static bending ≧ 4xOD

dynamic bending: ≥ 8xOD


50u" Gold plating contact pin

Operating Temperature : -10°C ~ 60°C


Ordering Information

Ref. No.

Volition™ Cat.6 ID Patch Cord UTP 1 meter, UTP, blue	VOL-6UP-ID1-B
Volition™ Cat.6 ID Patch Cord UTP 3 meter, UTP, blue	VOL-6UP-ID3-B
Volition™ Cat.6 ID Patch Cord UTP 5 meter, UTP, blue	VOL-6UP-ID5-B
Volition™ ID Patch Cord Test Cord	VOL-IDPC-TC



VOL-6UP-IDXX



VOL-IDPC-TC

Important Notice

The details contained in this literature have been carefully prepared from information available to 3M at the time of its production. However, it is not intended to be relied upon for purposes of product specification and you should contact your sales representative if specification details are required. Because of the wide variety of processes and conditions in which these products may be used, the user should first carry out tests to determine the suitability of the products for the particular use intended. All questions of warranty and liability relating to 3M products are governed by the selling 3M subsidiary's Terms of Sale subject where applicable to the prevailing law.

3M is trademark of the 3M company.

