



3M™ QSA disconnection module for 10 pair



QSA disconnection module for 10 pair

QSA disconnection module for 10 pair

The QSA disconnection module consists of 20 Insulation Displacement Contacts with disconnection facility. The IDC contacts are designed to be used with QSA/ LSA-PLUS approved IDC insertion tools.

For it's fixing, several QSA/ LSA-PLUS™ backmount frames are available.

Special disconnection plugs allow to disconnect the cable side from the jumper side. Furthermore, the 4-pole test cord allows separated line side and subscriber side testing.

Features

- System with a pitch of 22,5 mm
- Wire diameter from 0,4 - 0,8 mm
- Assembling on QSA/ LSA-PLUS backmount frames

Benefits

- Wide range of accessories
- Overvoltage protection available

Specifications

Technical characteristics

Contact principle:

Resilient contact design with insulation displacement according to DIN 41611 part 6

Contact termination:

Massive copper wires with diameter 0,4 – 0,8 mm (AWG 26-20) with an outer diameter of 0,7 – 1,6 mm (PE, foamed PE, PVC and PA). Flexible wires have to be tested individually.

Retermination:

Resilient contact design guarantees high quantity of re-terminations without influence on function and secures a gas tight connection.

Conductor range:

0,4 – 0,65 (AWG 26-22) > 200 x 0,8 (AWG 20) > 50 x no retermination with < 0,65 (AWG 22) after 0,8 (AWG 20)

Materials:

Housing: Polycarbonat, self extinguishing UL94 V-0

Colour: RAL 7035

Contacts: special brass alloy, silver-plated

Performance (typical values):

Contact resistance: < 10mΩ

Insulation resistance: > 5x10⁴ MΩ

Dielectric strength: > 2000 VAC / 50 Hz / 1 s
VDE 0472T.509

With stand test: > 4,0 kV (IEC 60-1)

Nominal operating current: < 5 A

Impulse discharge current: 10 kA (wave 8/20μs)

Cross Talk: At 1 MHz > 70dB

At 10 MHz > 55dB

At 20 MHz > 50dB

At 100 MHz > 35dB

Storage temperature range: -40...+90°C

Working temperature range: -40...+80°C

Ordering Information



3M™ QSA disconnection module for 10 pair

Ref.-No.

79103-510 40

3M is a trademark of 3M company, USA.

Important Notice

The details contained in this literature have been carefully prepared from information available to 3M at the time of its production. However, it is not intended to be relied upon for purposes of product specification and you should contact your sales representative if specification details are required. Because of the wide variety of processes and conditions in which these products may be used, the user should first carry out tests to determine the suitability of the products for the particular use intended. All questions of warranty and liability relating to 3M products are governed by the selling 3M subsidiary's Terms of Sale subject where applicable to the prevailing law. LSA-PLUS is a trademark of the TE Connectivity Ltd. family of companies.



3M Telecommunications

Europe, Middle East & Africa

c/o 3M Deutschland GmbH

Carl-Schurz-Straße 1

41453 Neuss · Germany

Tel.: ++49 (0)2131 / 14-5999

Fax: ++49 (0)2131 / 14-5998

Internet: www.3MTelecommunications.com

Please recycle. Printed on recycling paper.

Rights reserved to make technical alternations.

Copyright 2013, 3M Company, USA

Ref.No. 07-404-80500 Rev. A / 05.2013 JR